## ernitec

## **Vega 3**600TVL indoor Mini Dome



The Vega/3 CL-2V11 is the latest generation of the popular Vega indoor mini dome. It is an electronic day/night camera with a very high resolution of 600 TVL in colour mode and 650 TVL in b/w mode.

The Vega/3 includes an On-Screen-Display (OSD) menu for easy configuration of the camera. The configuration of the mini dome is made even faster by using the easily accessible service video output.

Other features include up to 4 programmable privacy zones. The size and location of each privacy zone is independently programmable.

The lens is a 2.8 - 10.5 mm varifocal with DC iris which makes it suitable for most indoor applications.

The Vega mini dome can operate on either 12 VDC or 24 VAC.

The dimensions and mounting holes on the Vega/3 are identical to the Vega/2 thereby providing an easy retrofit into existing installations.

## Features:

Electronic day/night camera
High resolution - 600 horizontal TV lines
Integrated 2.8–10.5 mm varifocal lens
0.1 lux sensitivity in colour mode
3-axis adjustment for wall or ceiling mount
4 privacy masks
OSD Menu for easy configuration
Auto white balance
AGC, BLC, Flickerless
12VDC/24VAC supply
Service video output for easy adjustment



## **Specification**

Model	VEGA/3 CL-2V11
Camera type	Electronic Day/Night
Video Output	1Vpp, 75Ω, PAL Composite
Image Sensor	1/3" SONY SuperHAD CCD II
Scanning System	2 :1 Interlace / H :15.625KHz , V : 50.0Hz
Total / effective pixels	470k / 440k
Horizontal Resolution	Colour : 600 TVL B/W: 650 TVL
Sensitivity, 30 IRE, F2.0	Colour : 0.1 lux B/W : 0.03 lux
S/N Ratio	>50 dB (AGC OFF)
Shutter speed	1/50 – 1/120.000 sec.
Synchronisation	50 Hz, internal
Lens	2.8 – 10.5 mm DC Iris, F1.2 (wide), F2.6 (tele)
IR Cut filter	Yes
Adjustment	3-axis (pan, tilt, rotate)
OSD	Yes, English
Privacy Masking	4 zones
Mirror function	Horizontal
AGC	On / Off
BLC	Off, Low, Middle , High
White Balance	Auto / Set
Flickerless	On/Off
Digital Noise Reduction	Off, Low, Middle, High
Power Range	10-15 VDC / 20-28 VAC
Power Consumption	3.6W ( Max )
Operating temperature and humidity	-10°C to ~ +45°C, 10 - 85% R.H.
Storage temperature and humidity	-20°C to ~ +55°C, 0 - 90% R.H.
Overall Camera Dimensions	Height 102mm (4.02") Diameter 100mm (3.94")
Weight	366g net.
Part number	0017-04214

