



- > 8ch real-time recording NVR
- > Up to 240fps recording in 1080p resolution
- > Build-in 100w 8ch POE switch
- > Up to 4 internal SATA hard drive
- > 40Mbps network throughput
- > VGA and Digital Display monitor output
- > Smart phone and Tablet viewer
- > Built-in web GUI
- > 4 year Warranty

The Ernitec network EDNS P6008 NVR is a premium network video recorder supporting 1080p local display and IP camera Plug & Play automatic installation.

Additionally, the EDNS P6008 NVR integrates IP camera dual streaming function and 8 ports PoE switch. It is an ideal recording solution for system integrators and installers applicable from small convenience stores and merchandise stores to medium-sized surveillance systems and projects.

With local display output ports, the EDNS P6008 NVR offers users Full HD crystal clear video on local monitor without additional devices. Integrated Plug & Play system, the EDNS P6008 NVR provides users up to 8 channels of IP camera connection without network, user name, password and other complicated settings.



Supporting IP cameras dual streaming function and embedded with 8 ports Power over Ethernet switch, the EDNS P6008 NVR is a perfect storage allowing system integrators to reduce expenditure on network bandwidth and equipment's, camera power supplies, cabling and installations.

The RemoteManager-II software provides EDNS P6008 NVR users a scalable solution for project applications. Moreover, users are able to monitor remotely by using iPhone, iPad and Android smart phones in the markets.

Technical Specification – Ernitec EDNS P6008

System		Storage	
Operating System	Embedded Linux	Build-in Storage	-
IP camera Input	8x RJ45 10/100Mbps with 100w POE, IEEE802.3af	Build-in Storage Interface	4 x SATA for 4 x 3.5" Hard disk
Network Port (Uplink)	RJ45, 10/100/1000Mbps Ethernet, support PPPoE/DDNS/ DHCP	External Storage Interface	1 x eSATA
Maximum Camera Network Throughput	40Mbps	Export	2 x USB 2.0 /1 x eSATA
Compression Method (Camera Dependent)	H.264 BL, H.264 MP, MJPEG	Alarm	
Camera Support		Alarm Input	8 x Terminal Block (TTL)
Plug'n Play supported cameras	Ernitec Vega SX series, Ernitec Mercury SX series, Ernitec Hawk SX series, Ernitec SX series, Ernitec Orion SX series	Alarm Relay Output	2 x Terminal Block (TTL)
Other camera support	Onvif profile S	Alarm Detection	N.C. / N.O. / Programmable
Live View and Playback		Motion Detection	Supported (camera dependent)
Monitor Output (VGA / Digital Display)	1024x768, 1280x1024, 1920x1080p	Video Loss Detection	Programmable
Monitor Output Live View / Playback (Camera Dependent)	120fps@1080p 240fps@720p 480fps@480p	General	
Playback Channel	1 / 2 / 4 / 8 / 16 Channels Simultaneous Playback	IR Remote	yes
Playback Mode	Forward, Reverse, Step-by-Step and Different Speed Play	Remote Control Software	RemoteManager-II
Playback Search	Calendar and Event	Remote Operation	Monitoring, Playback, Recording, System setup, Dome camera control, Archiving
Recording		Unit Dimension (W x H x D)	440 x 90 x 450mm (2U 19")
Recording Mode	Continuous, Schedule, Alarm, Motion Detection	Unit Weight (without storage)	6.0 kg
Pre-alarm	yes	Package Dimension (W x H x D)	563 x 197 x 558mm
Max Recording Rate	240fps@1080p 240fps@720p 240fps@480p	Package Weight (without storage)	10.0 kg
Recording Quality	Camera Dependent	Operation temperature	0°C to +40°C
Image Size	Camera Dependent	Operation humidity	10% to 90%
Data Lifetime	yes (programmable)	Power requirements	100V -240V AC/50-60Hz/300W
		Power unit	Internal PSU
		Languages	DE, DK, ES, FI, FR, IT, NL, NO, PL, SE, UK
		warranty	4 years
		Included accessories	IR remote, Quick guide, User Manual, Rack mount bracket, RemoteManager-II software DVD, UK and Schuko power cable
		Part Number	0064-06008

Optional accessories	
500GB NVR Storage Hard disk	HDD-500GB
1TB NVR Storage Hard disk	HDD-1000GB
2TB NVR Storage Hard disk	HDD-2000GB
3TB NVR Storage Hard disk	HDD-3000GB
Ernitec Go App	free download



DISTRIBUTED BY

