

Pegasus E1800R-48TB

8bay Rack Surveillance Server

- Appliance NVR Server
- 16-64 Channels
- 1800 FPS x 720P Recording
- Dual Gigabit Network Card
- 8 Hot Swappable HDD bays
- ESR or Milestone XProtect Option
- Embedded Windows® OS in RAID 1
- Dual SSD system discs
- Dual Power Supply
- 3 year Warranty



1800 Megapixel

The E1800R-48TB is a powerful video surveillance recorder that's optimized to work with CCTV recording Software for sensitive & long-term storage of IP/Megapixel cameras.

Optimized for Surveillance

The E1800R-48TB is engineered to optimize the way the processor, memory, graphics, OS and software technology work together to deliver massive recording power.

Tuned and Tested

All systems have been hardware tested over 24 together with more than 60 unique systems settings before leaving the assembling line to make sure that the server will run 24 hours per day, year after year.

Embedded OS

For high speed performance and system security this appliance NVR server is fitted with two solid state drives, these drives are set in a RAID 1 configuration with the embedded windows operating system loaded in our factory.

Hardware Monitoring

Optional special hardware management software and the ESR INFO notification server give you early warnings if a problem is detected so you can keep your server health.

Dual Power Supply

The E1800R-48TB has the benefit of a dual power supply, so if one fails your notified and a replacement can be changed with the server still running with no down time for your CCTV system.

Upgrade options

Customize options for the Build-ERS surveillance server, enables you to design the server to the project requirements. All hard drives are Enterprise performance rated which are optimized for 24/7 surveillance use. The hardware 8ch RAID controller supports 1.5, 3.0 and 6.0 Gb/s SAS and SATA data transfer rates on all channels and the professional graphics card renders pristine image quality on up to four Display Port monitors at resolutions up to 2560 x 1600 per output .

Drive Options

SATA Drives

Build-1TB-SATA-HDD-ESR	24/7 HDD SATA industrial 7200rpm
Build-2TB-SATA-HDD-ESR	24/7 HDD SATA industrial 7200rpm
Build-3TB-SATA-HDD-ESR	24/7 HDD SATA industrial 7200rpm
Build-4TB-SATA-HDD-ESR	24/7 HDD SATA industrial 7200rpm
Build-6TB-SATA-HDD-ESR	24/7 HDD SATA industrial 7200rpm

SAS Drives

Build-1TB-SAS-HDD-ESR	24/7 HDD SAS, 7200rpm optimized for RAID controller
Build-2TB-SAS-HDD-ESR	24/7 HDD SAS, 7200rpm optimized for RAID controller
Build-3TB-SAS-HDD-ESR	24/7 HDD SAS, 7200rpm optimized for RAID controller
Build-4TB-SAS-HDD-ESR	24/7 HDD SAS, 7200rpm optimized for RAID controller
Build-6TB-SAS-HDD-ESR	24/7 HDD SAS, 7200rpm optimized for RAID controller
Build-300GB-SAS-15K-HDD-ESR	24/7 HDD SAS, 15000rpm optimized for RAID controller

SSD Drives

BUILD-512GB-SSD-HDD-ESR	24/7 HDD SSD for high speed live database requirements
BUILD-1TB-SSD-HDD-ESR	24/7 HDD SSD for high speed live database requirements



RAID

Build-8ch-RAID-controller	8ch controller, 6 GB/s per port, 0,1,5,6,10,50,60 + hot spare
Build-RAID0-Setting	RAID config setting
Build-RAID1-Setting	RAID config setting
Build-RAID5-Setting	RAID config setting
Build-RAID10-Setting	RAID config setting
Build-RAID50-Setting	RAID config setting
Build-RAID6-Setting	RAID config setting
Build-RAIDJOB-Setting	RAID config setting
Build-hotspare	RAID config setting

Operating System

BUILD-WIN2012R2-STD-ESR	OS upgrade option to Windows Server 2012
Build-Upgrade-OS-SSD-2-ESR	Upgrade OS drive to two SSD drive



CPU

BUILD-CPU-UPGRADE TO 1800MP-ES	INTEL XEON E3-1245V3, 3,3GHz LGA1150 upgrade option for Build-ESR600
--------------------------------	--

Graphic controller

Build-ERC-4monitor	Graphic card for 4 monitors with 4 display port or 4 DVI output
--------------------	---

Upgrade options

Customize options for the Build-ERS surveillance server, enables you to design the server to the project requirements. This includes installation of analog capture cards for hybrid recorders and Ernitec EVR VMS software all pre loaded in our factory.



Software Options

BUILD-EVR	Factory installation of Ernitec EVR VMS
BUILD-EVR-PRO-1	Factory installation of Ernitec EVR Pro Version, 1 channel IP NVR & DVR license, Max 5 users, 1 server, 50 cameras per server.
BUILD-EVR-ENT-1	Factory installation of Ernitec EVR Enterprise Version, 1 channel IP NVR & DVR license, max 10 users, 5 servers, 64 cameras per server

Software Options

BUILD-VCA-1CH-A	Factory Installation of 1 Channel Video Analytics Advance Surveillance with people counting
-----------------	---



Capture Card

BUILD-EVR-16ANA-CARD-ONLY	Factory installation of 16 Channel High performance H264 Hybrid capture card, hardware compression with full D1 resolution on all channels resolution up to 400fps@D1 (704 x 576 pixels) BUILD-ESR600 will accept 2 x 16ch Analog capture cards
---------------------------	---

Follow us on



© 2015 Ernitec. All rights reserved
www.ernitec.com

Ernitec
Tempovej 41
2750 Ballerup
Denmark

Technical Specification Pegasus E1800R-48TB

Features

Recording Bit Rate	Up to 230Mbit / sec.
System Hard drive with OS	2 x 120Gb SSD in RAID 1 (1+1)
Optical drive	DVD-RW
Graphic controller for 2 monitor output	**1GB - 1xVGA, 1xDVI-D, 1xHDMI , 1xThunderbolt (up to 2560x1600)
Ernitec ESR software	Optional
Milestone Xprotect Corp	Optional

Auto-rebooting after power failure	Yes
------------------------------------	-----

Storage

Storage interface	SATA / SAS with RAID controller option
Storage included	48TB 8x 6TB RAID 5
Storage bays	8 x 3,5" hot swap bays
RAID controller	8ch controller, 6 GB/s per port, 0,1,5,6,10,50,60 + hot spare
Storage hard drive options	see upgrade options for more info

OS support

OS	Windows 7 Standard Embedded SP1 64bit
Upgrade option; Win OS	Windows 2012R2 64bit

CPU / Memory

CPU	INTEL Core I7-4770 3,4GHz
Memory	2x 8GB DDR3 1333MHz (16GB)

Cooling

Fan type	80x38mm 4-pin PWM Fans
Hot swap Fan	3

On-Board Devices

Keyboard / mouse	USB connector
Chipset	Intel® C226 Express PCH
Audio	HD Audio 7.1 channel connector by Realtek ALC1150
USB ports	8x USB 3.0 (4 rear + 4 via headers) 6xUSB 2.0 (2 rear + 4 via headers)
Network card	Dual Gigabit Ethernet LAN ports (1x Intel® i217LM & 1x Intel® i210AT)
Embedded RAID Controller	Embedded Onboard RAID for system hard drive

Optional I/O

Input output module	HWg-Juno 404 Ethernet I/O box (PSIA)
---------------------	--------------------------------------

Power

Redundant PSU	720W (1+1) high-efficiency (94%+) AC-DC Redundant power supplies with PM Bus and I2C
Power requirements	100v -240V AC/50-60Hz/720W

Management

Power Configurations	ACPI / ACPM Power Management, Main Switch Override Mechanism, Wake-On-LAN (WOL) header, Keyboard Wakeup from Soft-Off, Power-on mode for AC power recovery
Software	SuperDoctor III

Dimensions / Weights

Form Factor	2U 19" Rack Frame
Rack Rails	Yes
Dimensions (HxWxD mm)	89x437x648
Weight	31KG

General

Languages	25 including : English, German, French, Spanish, Dutch, Danish, Italian, Finnish
Operation conditions	Temperature range from +5°C to +35°C
Operating Relative Humidity Range	8% ~ 90% (non-condensing)
Warranty	3 years
Included accessories	1x OPTICAL MOUSE BLACK/USB PS2, CAT6 2M GREY, CAT6 2M BLUE, Power Cord schuko 2M , Power 2M UK,
Part number	0075-00542-V9

DISTRIBUTED BY

*Tested with Ernitec DVMS 6.4.3 and Ernitec Mercury SX302IR
 ** *Using different cables with the on board graphic card can cause small differences to the images on the monitors connected



We reserve the right to introduce product modifications without notice

Follow us on



© 2015 Ernitec. All rights reserved
 www.ernitec.com

Ernitec
 Tempovej 41
 2750 Ballerup
 Denmark

RO9EN0515