

Electronic “Easy” Day/Night Cameras

ernitec

Description

This range of electronic *Easy* Day/Night cameras includes cost-efficient, as well as highly advanced, fully featured models. Both mains supplied as well as low voltage versions are available.

Advanced DSP image processing replaces the costly traditional mechanical IR-cut filter.

Day/Night cameras should be combined with Infrared corrected Day/Night lenses. The IR-correction will ensure a perfectly focused picture under all lighting conditions, even when changing directly from infrared illumination to daylight.

Even when IR-illumination isn't used, using Day/Night-lenses will result in a sharper and crisper picture reproduction when used outdoor, due to the high IR-part of sunlight, compared to ordinary lenses.



Series ECB251



Series ECB231

ECB231

Cost-efficient Entry-level Electronic Day/Night Camera

- 1/3" 540 TVL
- Switch selection of AGC, BLC, D/N or Colour mode
- For DC Auto Iris or Manual Iris lenses

ECB251

High specification electronic Day/Night camera

- 1/3" **High-Res 540 TVL** Super HAD CCD-sensor
- On-Screen Display and Setup
- Privacy Masks
- Dynamic Noise Reduction (DNR)
- High-Res Y/C-SVHS output
- Easy Thumb-Wheel back focus setting

Specifications

Type	ECB231-DP-M / -D	ECB251-DP-D
Sensor format / CCD type	1/3" CS Sony CCD	1/3" CS / Super HAD
Video output	1 Vpp PAL	1 Vpp PAL
Horizontal resolution	540 TV Lines	540 TV Lines
Effective number of pixels	752x582	752x582
Minimum illumination, F1.2, AGC ON	0.01 lux @ 10 IRE 0.2 lux @ 50 IRE	0.03 lux @ 10 IRE 0.55 lux @ 50 IRE
Electronic shutter	Auto 1/50-1/100000 s	Auto 1/50-1/100000 s. / Manual (9 steps)
Iris Control modes	DC Auto, Manual (AES)	DC & Video Auto, Manual (AES)
S/N Ratio, AGC Off	50 dB	50 dB
Video synchronisation	Internal	Internal / Mains Lock
AGC	ON/OFF	Normal/Turbo/OFF
BLC – Backlight Compensation	ON (centre based) /OFF	ON (6 factory modes) / OFF
White Balance	Auto	Auto (2 modes) / Manual
Day/Night mode	ON/OFF	Auto (3 levels) / Colour / B & W
Gamma correction	0.45	0.45 / 1.0
Setup	Switches	OSD
Special Functions		
Camera ID	-	16 characters
Privacy Zones	-	8
Colour level adjustment	-	Yes
Dynamic Noise Reduction (DNR)	-	3 levels
Horizontal Picture Mirror function	-	Yes
Power supply		
Voltage	-M: 90-260 VAC -D: 12 VDC / 24 VAC ± 10%	12 VDC / 24 VAC ± 10%
Power consumption (max.)	3.5 W	6.0 W
Physical Characteristics		
Size (WxHxD)	48 x 46 x 115 mm	50 x 62 x 126 mm
Weight	Approx. 500 g.	Approx. 500 g.
Operating temperature	-10° to +50° C	-10° to +50° C
Humidity max.	90% RH	90% RH
Others		
Order info	0018-05023 / 0018-05024	0018-05021



Denmark Head Office
Ernitec A/S
Phone: +45 44 50 33 00
Fax: +45 44 50 33 33
info@ernitec.dk

French Branch Office
Ernitec SARL
Phone: +33 (0) 467 151 015
Fax: +33 (0) 467 640 181
info@ernitec.fr

German Branch Office
Ernitec GmbH
Phone: +49 (0) (40) 6756250
Fax: +49 (0) (40) 67562525
info@ernitec.de

UK Branch Office
Ernitec UK
Phone: +44 (0) 1903263125
Fax: +44 (0) 1903263126
info@ernitec.co.uk

Middle East Office
Ernitec ME
Phone: +961 1 751 796
Fax: +961 1 751 795
info@ernitecme.com

www.ernitec.com